

WHENEVER YOU SEE
COLOUR
THINK OF US



Introducing
SUPERIOR RANGE OF
**INTERIOR
EXTERIOR**



**PRODUCT
CATALOGUE**

Our Natural Products



Prakritik Emulsion

ECO-FRIENDLY COW DUNG PAINT

Nayur Prakritik Emulsion is a natural paint made from Cow Dung. It is a safe and healthy alternative to traditional paints. It is also eco-friendly and sustainable.

- | | |
|------------------------------|--|
| Method of Application | : Brush, Roller, Spray |
| Dilution | : Water Ratio 500ml. Per 1Ltr. |
| Drying Time | : Surface Dry 3-4 hrs. Hard Dry 24-28 hrs. |
| Usage | : Exterior & Interior |
| Coverage | : 150-200 sq.ft.* |
| Finish | : Matt |
| Available Size | : 20L, 10L, 4L, 1L. |



Prakritik Wall Primer

ECO-FRIENDLY COW DUNG PAINT

Nayur Prakritik Wall Primer is a natural paint made from Cow Dung. It is a safe and healthy alternative to traditional paints. It is also eco-friendly and sustainable.

- | | |
|------------------------------|--|
| Method of Application | : Brush, Roller, Spray |
| Dilution | : Water Ratio 500ml. Per 1Ltr. |
| Drying Time | : Surface Dry 3-4 hrs. Hard Dry 24-28 hrs. |
| Usage | : Exterior & Interior |
| Coverage | : 150-200 sq.ft.* |
| Finish | : Matt |
| Available Size | : 20L, 10L, 4L, 1L. |



Prakritik Acrylic Distemper

ECO-FRIENDLY COW DUNG PAINT

Nayur Prakritik Acrylic Distemper is a natural paint made from Cow Dung. It is a safe and healthy alternative to traditional paints. It is also eco-friendly and sustainable.

- | | |
|------------------------------|--------------------------------|
| Method of Application | : Brush, Roller |
| Dilution | : Water Ratio 600ml. Per 1 Kg. |
| Drying Time | : Surface Dry 4-6 hrs. |
| Usage | : Interior |
| Coverage | : 85-100 sq.ft.* |
| Finish | : Matt |
| Available Size | : 20Kg, 10Kg, 5Kg, 1Kg. |



Our Stainer & Booster Product



Nayur

EPOXY PRO WATERPROOF GLUE

FOR ROOF REPAIR

Nayur Epoxy Waterproof Sealer (Super Glue) for leakage protection of indoor & outdoor cracks. It is a transparent, odourless glue with high strength & Super Strong Bond.

Available Size : 4Ltr, 1Ltr, 500ml.



Nayur WATERPROOFING BOOSTER

SUPERIOR QUALITY

Nayur Waterproofing Booster is a high-performance additive designed to enhance the strength, smoothness, and adhesion of wall putty. It improves workability, reduces cracking, and ensures a superior finish. Ideal for both interior and exterior surfaces, it extends durability and boosts overall application efficiency.

Available Size : 5Ltr, 1Ltr.

Our Distemper Products



NAYUR

COLOUR TO OCCASION Acrylic Washable Distemper

Nayur Acrylic Washable Distemper is a premium quality, durable, water base interior wall finish. It can be applied on ceilings and walls where a beautifying matt finish, free from irritating glares due to light reflection is desired. It is a value for money product that makes it possible for consumers to have beautiful walls at affordable prices.

Method of Application	: Brush, Roller
Dilution	: Water Ratio 600ml. Per 1 Kg.
Drying Time	: Surface Dry 4-6 hrs.
Usage	: Interior
Coverage	: 85-100 sq.ft.*
Finish	: Matt
Available Size	: 20Kg, 10Kg, 5Kg, 1Kg.



NAYUR

COLOUR TO OCCASION

Acrylic Washable Distemper

Nayur Acrylic Washable Distemper is a premium quality, durable, water base interior wall finish. It can be applied on ceilings and walls where a beautifying matt finish, free from irritating glares due to light reflection is desired. It is a value for money product that makes it possible for consumers to have beautiful walls at affordable prices.

Method of Application	: Brush, Roller
Dilution	: Water Ratio 600ml. Per 1 Kg.
Drying Time	: Surface Dry 4-6 hrs.
Usage	: Interior
Coverage	: 85-100 sq.ft.*
Finish	: Matt
Available Size	: 20Kg, 10Kg, 5Kg, 1Kg.



Our Primer Products



SUPER

WALL PRIMER

WATER THINNALE
PREMIUM PRIMER
INTERIOR & EXTERIOR

Nayur Super Wall Primer is a foundational coating applied before paint to seal the surface, improve adhesion, and create a uniform base for a smoother, more durable, and longer-lasting paint job. It helps to cover imperfections, block stains from showing through, and ensures truer, more vibrant colors, especially when making large color changes

Method of Application	: Brush, Roller, Spray
Dilution	: Water Ratio 500ml. Per 1Ltr.
Drying Time	: Surface Dry 3-4 hrs. Hard Dry 24-28 hrs.
Usage	: Exterior & Interior
Coverage	: 150-200 sq.ft.*
Finish	: Matt / Gloss
Available Size	: 20L, 10L, 4L, 1L.





Signature Premium Quality EMULSION FOR INTERIOR USE

Nayur Signature Premium Emulsion is a premium high performance coating for Interior walls, based on pure acrylic emulsion which gives tough adhesion, flexibility & controls fungal and algae growth.

Method of Application	: Brush, Roller, Spray
Dilution	: Water Ratio 500ml. Per 1Ltr.
Drying Time	: Surface Dry 3-4 hrs. Hard Dry 24-28 hrs.
Usage	: Exterior & Interior
Coverage	: 150-200 sq.ft.*
Finish	: Matt / Gloss
Available Size	: 20L, 10L, 4L, 1L.



SMART DUAL EMULSION

Nayur Smart Dual Emulsion is best suited for application on walls in dry moderately humid climatic condition. It is an acrylic co-polymer, emulsion based wall coating. It's unique formulation ensures that the product has excellent adhesion to different types of surfaces like cement plaster, asbestos etc.

Method of Application	: Brush, Roller, Spray
Dilution	: Water Ratio 500ml. Per 1Ltr.
Drying Time	: Surface Dry 4 hrs.
Usage	: Exterior & Interior
Coverage	: 110-125 sq.ft.*
Finish	: Matt / Gloss
Available Size	: 20L, 10L, 4L, 1L.



XATRACME EXTERIOR EMULSION

Nayur Xatracme Exterior Glossy Emulsion is a premium high performance coating for Exterior walls, based on pure acrylic emulsion which gives tough adhesion, flexibility & controls fungal and algae growth.

Method of Application	: Brush, Roller, Spray
Dilution	: Water Ratio 500ml. Per 1Ltr.
Drying Time	: Surface Dry 4 hrs.
Usage	: Exterior
Coverage	: 130-150 sq.ft.*
Finish	: Matt / Gloss
Available Size	: 20L, 10L, 4L, 1L.





MAESTRO XTRASHINE EMULSION

Nayur Maestro Xtra Shine Interior Emulsion is a premium high performance coating for interior walls, based on pure acrylic emulsion which gives tough adhesion, flexibility & controls fungal and algae growth.

Method of Application	: Brush, Roller, Spray
Dilution	: Water Ratio 500ml. Per 1Ltr.
Drying Time	: Surface Dry 4 hrs.
Usage	: Interior
Coverage	: 110-125 sq.ft./ltr.* 2 Coats
Finish	: Matt / Gloss
Available Size	: 20L, 10L, 4L, 1L.



Multiple DUAL PREMIUM EMULSION

**EASY WASH
PREMIUM EMULSION
INTERIOR & EXTERIOR**

Nayur Multiple Premium Dual Emulsion is best suited for application on walls in dry moderately humid climatic condition. It is an acrylic co-polymer, emulsion based wall coating. It's unique formulation ensures that the product has excellent adhesion to different types of surfaces like cement plaster, asbestos etc.

Method of Application	: Brush, Roller, Spray
Dilution	: Water Ratio 500ml. Per 1Ltr.
Drying Time	: Surface Dry 4 hrs.
Usage	: Exterior
Coverage	: 110-125 sq.ft./ltr.*
Finish	: Matt / Gloss
Available Size	: 20L, 10L, 4L, 1L.



Superior

**Durable Sheen Finish
PREMIUM EMULSION
DUST PROOF EXTERIOR**

Nayur Superior Premium Dust Proof Exterior Emulsion is best suited for application on walls in dry or moderately humid climatic conditions. It is an acrylic co-polymer, Emulsion based wall coating. It's unique formulation ensures that the products has excellent adhesion to different types of surfaces like cement plaster, asbestos etc.

Method of Application	: Brush, Roller, Spray
Dilution	: Water Ratio 500ml. Per 1Ltr.
Drying Time	: Surface Dry 4-6 hrs. Hard Dry 26-28 hrs.
Usage	: Exterior
Coverage	: 1 Coat: 1.7-1.8 sqm/L* - 2 Coats: 0.9-1 sqm/L*
Finish	: Matt / Gloss
Available Size	: 20L, 10L, 4L, 1L.



Our Platinum Products



XATRACME ADVANCE+ DUST PROOF & WEATHERPROOF

Nayur Xatracme Advance Exterior Emulsion is best suited for application on walls in dry or moderately humid climatic conditions. It is an acrylic co-polymer, Emulsion based wall coating. It's unique formulation ensures that the products has excellent adhesion to different types of surfaces like cement plaster, asbestos etc.

Method of Application	: Brush, Roller, Spray
Dilution	: Water Ratio 500ml. Per 1Ltr.
Drying Time	: Surface Dry 4-6 hrs. Hard Dry 26-28 hrs.
Usage	: Exterior
Coverage	: 1 Coat: 1.7-1.8 sqm/L* - 2 Coats: 0.9-1 sqm/L*
Finish	: Matt / Gloss
Available Size	: 20L, 10L, 4L, 1L.



Signature

DIAMOND SHINE EMULSION FOR INTERIOR USE

Nayur Signature Diamond Shine Emulsion is a premium high performance coating for Interior walls, based on pure acrylic emulsion which gives tough adhesion, flexibility & controls fungal and algae growth.

Method of Application	: Brush, Roller, Spray
Dilution	: Water Ratio 500ml. Per 1Ltr.
Drying Time	: Surface Dry 4 hrs.
Usage	: Exterior
Coverage	: 110-125 sq.ft./ltr.*
Finish	: Matt / Gloss
Available Size	: 20L, 10L, 4L, 1L.



NAYUR COLOUR TO OCCASION

Metallic Paint GOLD - SILVER

Nayur Metallic enamel paint is a durable, protective coating that dries to a hard, glossy finish with a reflective, shimmering effect. It's commonly used for decorative and protective purposes on both indoor and outdoor surfaces, especially metal and wood.



Superior

Durable Sheen Finish SINGLE RED EMULSION DUST PROOF EXTERIOR

Nayur Superior Dust Proof Exterior Single Red Emulsion is best suited for application on walls in dry or moderately humid climatic conditions. It is an acrylic co-polymer, Emulsion based wall coating. It's unique formulation ensures that the products has excellent adhesion to different types of surfaces like cement plaster, asbestos etc.

Method of Application	: Brush, Roller, Spray
Dilution	: Water Ratio 500ml. Per 1Ltr.
Drying Time	: Surface Dry 4-6 hrs. Hard Dry 26-28 hrs.
Usage	: Exterior
Coverage	: 1 Coat: 1.7-1.8 sqm/L* - 2 Coats: 0.9-1 sqm/L*
Finish	: Matt / Gloss
Available Size	: 20L, 10L, 4L, 1L.



Our Oil Based Products



Nayur HI-GLOSS SYNTHETIC ENAMEL PREMIUM MULTI-PURPOSE PAINT

Nayur High gloss enamel is a durable, reflective paint that provides a mirror-like, high-shine finish, making it ideal for surfaces like doors, windows, and trim. It's known for its tough, protective film, long-lasting gloss, and excellent durability, often used on both interior and exterior surfaces, including wood, metal, and masonry.

- Method of Application** : Brush, Spray
Dilution : MTO Ratio 200ml. Per 1Ltr.
Drying Time : Surface Dry 4-6 hrs. Hard Dry 26-28 hrs.
Usage : Exterior / Interior
Coverage : 1 Coat: 1.7-1.8 sqm/L* - 2 Coats: 0.9-1 sqm/L*
Finish : Matt / Gloss
Available Size : 20L, 4L, 1L, 500ml, 200ml, 100ml, 50ml.



AVAILABLE SHADES



Nayur PREMIUM DUAL PRIMER PREMIUM MULTI-PURPOSE PAINT

Nayur Red oxide primer is a protective, rust-inhibiting coating primarily used on ferrous metal surfaces like iron and steel. It prevents corrosion, improves the adhesion of the topcoat, and provides a strong, long-lasting base for painted surfaces like gates, grills, and machinery. It's important to properly clean and prepare the metal surface before application for the best results.

- Method of Application** : Brush, Spray
Dilution : MTO Ratio 200ml. Per 1Ltr.
Drying Time : Surface Dry 4-6 hrs. Hard Dry 26-28 hrs.
Usage : Exterior / Interior
Coverage : 1 Coat: 1.7-1.8 sqm/L* - 2 Coats: 0.9-1 sqm/L*
Finish : Matt / Gloss
Available Size : 20L, 4L, 1L, 500ml, 200ml, 100ml, 50ml.



Our Powder Products





SCAN QR CODE



NAYUR PAINTS

GREATER NOIDA (NCR)-203141

E-mail: nayurpaints@gmail.com, Contact us: 09837435780, 08057135780

